



NOTES:

1. PRIMARY DIMENSION IN INCHES. SECONDARY DIMENSIONS IN (mm).
2. CLUTCH WILL FUNCTION WITH ANY RADIUS FACED BEARING FROM 44mm TO 52mm DIA. 44mm BEARING HIGHLY RECOMMENDED FOR BEST FEEL AND LOWEST RELEASE LOAD.
3. ILLUSTRATED WITH DISC PACK P/N: 64185-4-VTV-36. DISCS SOLD SEPARATELY.

CLUTCH P/N:	# OF DISCS	FLYWHEEL MOUNTING	SETUP HEIGHT (NEW)	SETUP HEIGHT (WORN)	BOLT GRIP	OVERALL HEIGHT
66-001__	1	STEP	.81 (20.6)	.96 (24.4)	.880 (22.35)	1.55 (39.4)
66-002__	2	STEP	1.09 (27.7)	1.24 (31.5)	1.159 (29.44)	1.83 (46.5)
66-012__	2	POT	1.09 (27.7)	1.24 (31.5)	1.059 (26.90)	1.73 (43.9)
66-003__	3	STEP	1.37 (34.8)	1.52 (38.6)	1.442 (36.63)	2.11 (53.6)
66-013__	3	POT	1.37 (34.8)	1.52 (38.6)	1.342 (34.09)	2.01 (51.1)
66-004__	4	STEP	1.61 (40.9)	1.76 (44.7)	1.725 (43.82)	2.39 (60.7)
66-014__	4	POT	1.61 (40.9)	1.76 (44.7)	1.625 (42.28)	2.29 (58.2)