



HAWK PERFORMANCE DYNAMIC TORQUE CONTROL BRAKES

HAWK PERFORMANCE FERRO-CARBON BRAKES

COMPOUND

REMARKS

DTC-70
Letter Code U

- **Optimal Temperature Range**
400-1600°F; 204-871°C
 - High Temp
 - High Torque
 - Excellent Torque Control
 - Excellent Modulation and Release Characteristics
- Designed for High Deceleration Rates**
Supersedes HT-15 material

DTC-60
Letter Code G

Note: Slightly lower torque than DTC-70. Recommended for use with DTC-70 when split friction between front and rear axle is desired

- **Optimal Temperature Range**
400-1600°F; 204-871°C
- High Temp
- High Torque
- Excellent Torque Control
- Excellent Modulation and Release Characteristics

DTC-30
Letter Code W

- **Optimal Temperature Range**
100-1200°F; 38-649°C
- Wide Temp Range
- Controllable Torque
- Smooth Feel and Bite
- Excellent Release Characteristics

DTC-05
Letter Code H

- **Optimal Temperature Range**
100-900°F; 38-482°C
 - Low to Mid Temp Range
 - Smooth, Predictable Torque
- Designed to Provide Lower Torque**

COMPOUND

REMARKS

HT-14
Letter Code V
Note: See DTC-60 and DTC-70 for latest material development

- **Optimal Temperature Range**
300-1400°F; 149-871°C
 - High Temp
 - High Torque
- Designed for High Deceleration Rates**

HT-10
Letter Code S

- **Optimal Temperature Range**
300-1300°F; 149-871°C
 - High Temp
 - Intermediate to High Torque
- Designed for High Deceleration Rates**

Blue 9012
Letter Code E
Note: See DTC-60 for latest material development

- **Optimal Temperature Range**
250-1000°F; 121-538°C
 - Low to Mid Temp
 - Low to Intermediate Torque
 - Excellent Modulation
- Multi-Purpose Compound**

Black
Letter Code M

- **Optimal Temperature Range**
100-900°F; 38-482°C
- Lower Temp
- Low to Intermediate Torque

DR-97
Letter Code J

- **Optimal Temperature Range**
100-900°F; 38-482°C
- Excellent Static and Dynamic Coefficient of Friction

PLEASE NOTE: HT-15 has become obsolete and therefore discontinued.



Compound Comparisons and Recommendations

Saloon & GT Car Race & Tarmac Rally (FRONT AXLE APPLICATIONS)

Vehicle Weight	Performance Categories	DTC-70	DTC-60	HT-14	HT-10	BLUE 9012	BLACK
Over 1275 kg	Initial Torque	5	5	5	5	5	NOT RECOMMENDED
	Fade Resistance	5	5	5	5	5	NOT RECOMMENDED
	Release	5	5	5	5	5	NOT RECOMMENDED
	Consistency	5	5	5	5	5	NOT RECOMMENDED
	Modulation	5	5	5	5	5	NOT RECOMMENDED
	Pad Wear	5	5	5	5	5	NOT RECOMMENDED
	Disc Wear	5	5	5	5	5	NOT RECOMMENDED
Under 1275 kg	Initial Torque	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
	Fade Resistance	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
	Release	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
	Consistency	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
	Modulation	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
	Pad Wear	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
	Disc Wear	5	5	NOT RECOMMENDED	5	5	NOT RECOMMENDED
Under 1050 kg	Initial Torque	5	5	NOT RECOMMENDED	5	5	5
	Fade Resistance	5	5	NOT RECOMMENDED	5	5	5
	Release	5	5	NOT RECOMMENDED	5	5	5
	Consistency	5	5	NOT RECOMMENDED	5	5	5
	Modulation	5	5	NOT RECOMMENDED	5	5	5
	Pad Wear	5	5	NOT RECOMMENDED	5	5	5
	Disc Wear	5	5	NOT RECOMMENDED	5	5	5

RATING SCALE: 1 ■ = Fair, 5 ■ = Excellent

Saloon & GT Car Race & Tarmac Rally (REAR AXLE APPLICATIONS)

Vehicle Weight	Performance Categories	DTC-70	DTC-60	HT-10	BLUE 9012	BLACK	HPS or DTC-05
Over 1275 kg	Initial Torque	5	5	5	5	5	5
	Fade Resistance	5	5	5	5	5	5
	Release	5	5	5	5	5	5
	Consistency	5	5	5	5	5	5
	Modulation	5	5	5	5	5	5
	Pad Wear	5	5	5	5	5	5
	Disc Wear	5	5	5	5	5	5
	Rear Lockup Resistance	5	5	5	5	5	5
Under 1275 kg	Initial Torque	5	5	5	5	5	5
	Fade Resistance	5	5	5	5	5	5
	Release	5	5	5	5	5	5
	Consistency	5	5	5	5	5	5
	Modulation	5	5	5	5	5	5
	Pad Wear	5	5	5	5	5	5
	Disc Wear	5	5	5	5	5	5
	Rear Lockup Resistance	5	5	5	5	5	5
Under 1050 kg	Initial Torque	NOT RECOMMENDED	5	5	5	5	5
	Fade Resistance	NOT RECOMMENDED	5	5	5	5	5
	Release	NOT RECOMMENDED	5	5	5	5	5
	Consistency	NOT RECOMMENDED	5	5	5	5	5
	Modulation	NOT RECOMMENDED	5	5	5	5	5
	Pad Wear	NOT RECOMMENDED	5	5	5	5	5
	Disc Wear	NOT RECOMMENDED	5	5	5	5	5
	Rear Lockup Resistance	NOT RECOMMENDED	5	5	5	5	5



Unit 40, Silverstone Circuit, Towcester, Northants, NN12 8TN, U.K.

Tel: +44 (0) 1327 857991

e: info@competitionsupplies.com

www.competitionsupplies.com

Single Seaters and Sports Prototypes

(FRONT AXLE APPLICATIONS) RATING SCALE: 1 ■ = Fair, 5 ■ = Excellent

Vehicle Weight	Performance Categories	DTC-70	HT-14	DTC-60	BLUE 9012	BLACK
Over 500kg	Initial Torque	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Fade Resistance	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Release	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Consistency	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Modulation	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Pad Wear	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Disc Wear	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
Under 500kg	Initial Torque	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Fade Resistance	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Release	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Consistency	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Modulation	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Pad Wear	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Disc Wear	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
Under 410kg	Initial Torque	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Fade Resistance	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Release	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Consistency	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Modulation	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Pad Wear	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Disc Wear	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■

Single Seaters and Sports Prototypes

(REAR AXLE APPLICATIONS)

Vehicle Weight	Performance Categories	DTC-60	HT-14	HT-10	BLUE 9012	BLACK
Over 500kg	Initial Torque	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Fade Resistance	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Release	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Consistency	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Modulation	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Pad Wear	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Disc Wear	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
	Rear Lockup Resistance	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
Under 500kg	Initial Torque	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Fade Resistance	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Release	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Consistency	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Modulation	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Pad Wear	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Disc Wear	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■
	Rear Lockup Resistance	NOT RECOMMENDED	NOT RECOMMENDED	■■■■■	■■■■■	■■■■■