

EWP® 130 Electric Water Pump 12 & 24 Volt



The world's first universal fit / remote mount Electric Water Pump. Suitable for naturally-aspirated and turbo/supercharged engines up to 5 litres.



Technical Specifications

	12 Volt Pump	24 Volt Pump
Operating voltage	3V DC to 15V DC	20V DC to 27V DC
Maximum current	10A @ 13V	5.5A @ 24V
Flow rate (max)	130 L/min (34.34 US gal/min) @ 13V DC	130 L/min (34.34 US gal/min) @ 24V DC
Operating temp.	-40° to 130°C (-40° to 266°F)	-40° to 130°C (-40° to 266°F)
Pump design	Clockwise centrifugal with volute chamber	Clockwise centrifugal with volute chamber
Pump weight	1,226 grams (2.7 lb)	1,226 grams (2.7 lb)
Pump material	Aluminium (powder coated)	Aluminium (powder coated)
Burst pressure	500 kPa (72.5 psi)	500 kPa (72.5 psi)
Seal	Ceramic face seal	Ceramic face seal
Fits hose sizes	35mm to 51mm (1 3/8" to 2")	35mm to 51mm (1 3/8" to 2")

Kit Contents

Description	12V	24V	Qty
EWP®130 Alloy 24 Volt Pump		✓	1
EWP®130 Alloy 12 Volt Pump	✓		1
Alloy elbow adaptor - 35mm (1 3/8")	✓	✓	1
Alloy straight adaptor - 35mm (1 3/8")	✓	✓	2
Hose Clamps	✓	✓	2
Rubber adaptor sleeve - 3mm (1/8")	✓	✓	1
O ring	✓	✓	2
Wiring harness	✓	✓	1
Hose clamps	✓	✓	2
Assorted hardware bag - includes 12V relay #0533	✓		1
Assorted hardware bag - includes 24V relay #0534		✓	1

Kit Options (12V & 24V)

Part #	Description	Qty
8304	Alloy straight adaptor - 38mm (1 1/2")	1*
8303	Alloy elbow adaptor - 38mm (1 1/2")	1*
8505	90° rubber hose adaptor - 38mm (1 1/2") ID	1*
8511	Rubber adaptor sleeve 6mm (1/4")	1*
1025	Alloy adaptor AN-16	1*
1026	Alloy adaptor - 1 1/4" NPT	1*
1027	Alloy adaptor straight - 25mm (1")	1*
1028	Alloy adaptor straight - 19mm (3/4")	1*

* 2 required if using at both ends

